




ACCESSORIES CDP 40 – CDP 50 – CDP 70 – CDP 40T – CDP 50T – CDP 70T

Illustration	Accessory	Description	CDP type	Dantherm no.
	Remote control, DRC1	DRC1 is a wireless RH and temperature controller. Frequency: 433 mhz Range: Up to 50 m depending on the conditions Protection class: IP20 Functionalities: • Reading and setting of RH, temperature, alarms and service information • Locking of settings	CDP 40 CDP 50 CDP 70 CDP 40T CDP 50T CDP 70T	093455
	External RH/t sensor	Remote sensor with 10 meter wire. Protection class: IPX7	CDP 40 CDP 50 CDP 70 CDP 40T CDP 50T CDP 70T	051710
	Floor mounting kit, 2 pcs.	Each bracket to be mounted on each side of the dehumidifier.	CDP 40 CDP 50 CDP 70	094322
	Water heating coil 2.6 kW*	Comprises water heating coil, flexible hose, fittings and gasket *at 80/60° C (See technical specifications for water heating coils on separate page).	CDP 40 CDP 40T	094333
	Water heating coil 4.2 kW*		CDP 50 CDP 50T	094334
	Water heating coil 6.2 kW*		CDP 70 CDP 70T	094335
	DN 10 control valve and actuator for water heating coils	Comprises valve and actuator 230 V, ON/OFF (180 seconds from closed to fully open), incl. union nut for Ø 12 tube.	CDP 40 CDP 50 CDP 70 CDP 40T CDP 50T CDP 70T	094340
	Electric heating coil 2 kW	Comprises electric heating coil, relays and electric wires.	CDP 40 CDP 40T	094336
	Electric heating coil 3.5 kW		CDP 50 CDP 50T	094337
	Electric heating coil 5 kW		CDP 70 CDP 70T	094338

ACCESSORIES CDP 40 – CDP 50 – CDP 70 – CDP 40T – CDP 50T – CDP 70T

Illustration	Accessory	Description	CDP type	Dantherm no.																													
	Pro 30 Standard Exhaust fan	<p>The exhaust fan can be used in combination with the CDP to either increase dehumidification capacity or establish outdoor air supply.</p> <p>Pro 30 Standard: Power supply: 230 V/50 Hz Power consumption: 7,5 W Air volume: 97 m³/h Sound level: 25 dB (A)</p>	<p>CDP 40 CDP 50 CDP 70 CDP 40T CDP 50T CDP 70T</p>	094339																													
	Pro 32 Standard Exhaust fan	<p>Pro 32 Standard: Power supply: 230 V/50 Hz Power consumption: 17 W Air volume: 185 m³/h Sound level: 32 dB (A)</p> <p>Dimensions:</p> <table border="1"> <thead> <tr> <th></th> <th>Pro 30 Standard</th> <th>Pro 32 Standard</th> </tr> </thead> <tbody> <tr> <td>∅D</td> <td>99</td> <td>124</td> </tr> <tr> <td>B</td> <td>158</td> <td>182</td> </tr> <tr> <td>H</td> <td>136</td> <td>158</td> </tr> <tr> <td>L</td> <td>107</td> <td>91</td> </tr> <tr> <td>L1</td> <td>26</td> <td>27</td> </tr> <tr> <td>D</td> <td>100</td> <td>125</td> </tr> <tr> <td>L2</td> <td>500</td> <td>500</td> </tr> <tr> <td>B2</td> <td>100</td> <td>125</td> </tr> <tr> <td>C</td> <td>125</td> <td>150</td> </tr> </tbody> </table>		Pro 30 Standard	Pro 32 Standard	∅D	99	124	B	158	182	H	136	158	L	107	91	L1	26	27	D	100	125	L2	500	500	B2	100	125	C	125	150	<p>CDP 40 CDP 50 CDP 70 CDP 40T CDP 50T CDP 70T</p>
	Pro 30 Standard	Pro 32 Standard																															
∅D	99	124																															
B	158	182																															
H	136	158																															
L	107	91																															
L1	26	27																															
D	100	125																															
L2	500	500																															
B2	100	125																															
C	125	150																															
	Through-wall duct kit with filter, extension kit and alu grill	<p>Comprises inlet and outlet section, grills, inlet filter and extension.</p> <p>For walls between 70 and 366 mm thickness.</p>	CDP 40T	094271																													
			CDP 50T	094243																													
			CDP 70T	093508																													
	Duct lead-in adapter	<p>The adapter makes it possible to place CDP 40T-50T-70T on the wall without changing the existing wall openings.</p>	CDP 40T	094801																													
			CDP 50T	094802																													
			CDP 70T	094804																													