1:1 SINGLE-SPLIT OUTDOOR UNIT R32

SHORAI EDGE



Highlights

Can be connected to one indoor unit Piping lengths up to max. 25 m Compact, quiet & durable



Compact and quiet outdoor units with low-GWP refrigerant R32 for 1:1 combination with SHORAI EDGE or CONSOLES indoor units. In a robust, weatherproof housing, can be set up flexibly.

Economical & reliable

- Very high energy efficiency (A +++)
- DC hybrid inverter technology
- _ Single (07 to 16) or twin rotary compressor (18 to 24)
- Particularly high efficiency in part load range
- Complies with the ECODESIGN Lot10 guideline
- Wide operating temperature range
- Housing made of galvanized sheet steel with a creamcolored stove enamel finish
- Large curved heat exchanger for a small footprint
- Automatic restart after power failure adjustable

Saving resources

- Inverter control minimizes power consumption
- Eco mode
- _ Environmentally friendly low-GWP refrigerant R32 pre-filled
- _ Air as an energy source in heating mode
- Inconspicuous design adapts to any environment
- _ SILENT whisper mode

Comfort and economy functions

- Operation via comfort IR remote control (included with the indoor unit)
- _ Clear & simple operation
- Automatic mode
- _ Hi power
- Comfort sleep
- Weekly timer with 4 freely programmable settings / day
- _ 28 time programs per week
- SILENT operating mode
- 8 ° C frost protection function
- Power Select
- Optional APP control via smartphone and tablet



TOSHIBA

SHORAI EDGE / SET

Indoor unit		RAS-B13J2KVSG-E	
Outdoor unit			RAS-13J2AVSG-E
Cooling capacity	kW	*	3,50
Cooling range (minmax.)	kW	*	1,00 - 4,10
Power consumption (min./nom./max.)	kW	*	0,25/0,90/1,12
Pdesign c	kW		3,50
Energy efficiency EER	W/W	*	3,89
Energy efficiency SEER		*	8,60
Energy efficiency class		*	A+++
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	۲	4,20
Heating range (minmax.)	kW	*	1,00 - 5,30
Power consumption (min./nom./max.)	kW	*	0,20/1,08/1,55
Pdesign h	kW		3,20
Energy efficiency COP	W/W	۲	3,89
Energy efficiency SCOP		۲	5,10
Energy efficiency class		۲	A+++
Outdoor temperature operating range (minmax.)	°C	۲	-15/+24

Indoor unit			RAS-B13J2KVSG-E
Sound pressure level (low/med/high)	dB(A)	*	19/23/43
Sound pressure level (low/med/high)	dB(A)	*	19/23/43
Sound power level	dB(A)	*	56
Sound power level	dB(A)	*	56
Airflow	m³/h		732
Dimensions (HxWxD)	mm		293 x 800 x 226
Weight	kg		10

🕸 Cooling 🔶 Heating



SHORAI EDGE / SET

Outdoor unit			RAS-13J2AVSG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	А		10
Current consumption (nom.)	А		3,89
Current consumption (max.)	А		5,35
Sound pressure level (low/med/high)	dB(A)	*	39/45/46
Sound pressure level (low/med/high)	dB(A)	÷.	43/46/48
Sound power level	dB(A)	*	56
Sound power level	dB(A)	*	61
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m³/h		1950
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,80
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		30

🏶 Cooling 📜 Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

Accessories	Description
Fernbedienung	Infrared remote control included
RB-N103S-G	TOSHIBA Home AC control - wireless WiFi control / Seiya (24), Shorai Edge, Shorai Premium (18,22,24), Daiseikai 9
818F0036	IAQ filter strips
818F0023	Active carbon-catechin filter strips
TCB-IFCB5-PE	External on/off PCB, window contact module
TCB-PX100-PE	Casing for outdoor installation of window contact module for high-wall units

quality in

- SHORAI EDGE

In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here: In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



Energy Label A+++: Energy efficiency class A+++ guarantees the lowest power consumption and the highest efficiency!

+

Hybrid inverter control: Smooth capacity regulation.



Rotary compressor: Reliability and high efficiency.

Auto diagnostic: Check of system for flawless operation.



R32: Used refrigerant: R32.

