

COMPARISON OF PICO MODELS



Model	Old model PICO		New model PICO		
	PICO HP2 WI	PICO HP2 WI-CO ₂	PICO BASIC	PICO PRO	PICO PRO+
Power supply	12V Needs an external power supply to fit in an external wall box		230V / 50-60 Hz		
Filter	2xG2		2xG2		
Wall hole size	100-125-150-200 Ø		100-125-150 Ø		
m ³ h max	28-46-74-91		30-45-60		
Sound pressure dB(A) max 1 m	34-40-46-50		32-37-41		
Automatic mechanical damper	No		No	Yes	
Wi-fi	Local connection by app (web page)		Remote or local (new app tecnosystemi)		
Finishing	Glossy white		Matt white		
Indicator	Led - always on		Led with light guide, possibility to turn off		
Speed	3 Speed (min - med - max)		4 Speed (night -min - med max) adjustable by app		
Master - Slave	Max 4 unit connected by cable		Max 4 unit connected by wireless (Slave configurable in asynchronous to synchronous mode)		
Accessories	Infrared remote included		Not included	Infrared remote included	
Firmware update by app	No		Yes		
Minimum wall thickness	310		270 mm (250mm changing external protection grid type)		
Home assistant	No		Compatible with amazon alexa and gogole home		

COMPARISON OF FUNCTIONS

Model		Pico Wi	NEW	NEW	NEW
			Pico Basic	Pico Pro	Pico Pro+
Regenerator		•	•	•	•
Extraction		•	•	•	•
Aeration		•	•	•	•
Humidity threshold	Regenerator	•	•	•	•
	Extraction	•	•	•	•
Natural Exchange		-	-	•	•
Free Cooling		•	-	-	•
Free Heating		•	-	-	•
CO ₂ threshold	Regenerator	•	-	-	•
	Extraction	•	-	-	•
Humidity CO ₂ threshold	Regenerator	-	-	-	•
	Extraction	-	-	-	•
Night mode		-	•	•	•
Master Slave		•	•	•	•

LEGEND: • function present
- function not present