



# ARTCOOL Stylist Smart Inverter

## LED & Mood Lighting

Ever-present, pervasive and pleasant, the ring of LED lighting creates a ring of illumination to you express you every mood.


### 1 Operational Light

The Operational LED Lighting pulses in response to your commands. Additionally, wind strength to temperature, every change is enlightening with Artcool Stylist on your wall.



### 2 Mood Lighting

From relaxing to romantic, LG puts you in total control with the ability to customize your color and create a palate of LED lighting. Warm, cool or classic, illuminate your personal space with just the right hue.



## Remote Control

When you're truly in control of your environment you feel safe and comfortable. Moreover everyone appreciates instant feedback and a quick view by smart alarm.




### 1 Innovative Remote Controller

Simple & intuitive control display fundamental multi-purpose function "Hot Key" for quick usage.



#### Key Function




### 2 Smart Alarm

The Smart alarm helps you to wake with a gradual lighting effect that mimics the rising sun.



## 3 way Soft Airflow

Provides softer and more natural airflow with 3-directional flow patterns.



### 1 Complete Silence 19dB

#### LG's Unique Skew Fan

By minimizing the surface pressure of the fan blade when in contact with the air therefore peak noise are reduced to a level that is among the lowest in the world.

#### BLDC Fan Motor

Precise speed control provides 13 different steps which makes operation smoother. Both electrical and mechanical noise is more silent, and high speed operation is available.


#### Active Low Vibration Control

A speed-error component estimates the load to compensate for imbalances, which are the primary causes of vibration and noise, enabling the rotation of the motor without vibration at low Hz levels.

### 2 3 way Airflow

LG air conditioner delivers cool air to every corner of your room.

The 3-way-swing function blows air quickly and efficiently in all directions.




## Wi-Fi Ready

Control your air conditioners with the smart internet devices via smartphones using a simple Android or iOS



### 1 Control the Air Conditioner

Easy access to your air conditioner with LG Wi-Fi Ready function.



\*Need to have a internet connection and register user account to IntesisHome via App.

### 2 Benefit



#### Wi-fi Ready Function

- On/Off
- Setpoint temperature
- Mode
- Vane control
- Fan speed

# ARTCOOL Stylist

## Smart Inverter



9K  
G09WL  
12K  
G12WL



Unit	9K		12K	
Model Indoor Unit	ASNW0963WB0		ASNW1263WB0	
Model Outdoor Unit	ASUW0963WB0		ASUW1263WB0	
<b>Indoor Unit</b>				
Capacity	Cooling	Min/Rated/Max	W	1300/2500/3500
	Heating	Min/Rated/Max	W	1300/3000/4200
	Heating -7°C	Rated	W	3200
Power Input	Cooling	Rated	W	690
	Heating +7°C	Rated	W	830
EER			W/W	3.61
S.E.E.R.				5.70
P design C			kW	2.50
COP			W/W	3.61
S.C.O.P.				3.80
P design H			kW	2.70
S.E.E.R.				5.7
S.C.O.P.				3.8
Energy Label	Cooling			A+
	Heating			A
Annual Energy Consumption	Cooling		kWh	170
	Heating		kWh	1100
Power Supply			∅ / V / Hz	1/220-240/50
Sound Pressure	Cooling	S/L/M/H	dBA	19/29/34/39
	Heating	S/L/M/H	dBA	32/35/39
Sound Power	Cooling	High	dBA	60
Air Flow Rate	Cooling	Max (Power)	m <sup>3</sup> /min	9.7
Air Flow Rate	Cooling	S/L/M/H	m <sup>3</sup> /min	4.5/6.0/7.0/8.0
	Heating	L/M/H	m <sup>3</sup> /min	6.6/7.5/8.5
Dehumidification Rate			l/h	1.2
Running Current	Cooling	Rated/Max	A	4/6.0
	Heating	Rated/Max	A	4/7.0
Starting Current	Cooling	Rated	A	4
	Heating	Rated	A	4
Circuit Breaker			A	15
Power Supply Cable			N x mm <sup>2</sup>	3*1.0
Power & Transmission Cable			N x mm <sup>2</sup>	4*1.0(Including Earth)
Dimension			mm	645*645*121
Net Weight			kg	18
Fan Motor Output			W	32.7
<b>Outdoor Unit</b>				
Operation Range	Cooling	Min-Max	°CDB	-10-48
	Heating	Min-Max	°CDB	-15-24
Sound Pressure	Cooling	High	dBA	45
	Heating	High	dBA	45
Sound Power	Cooling	High	dBA	65
Air Flow Rate	Cooling	High	m <sup>3</sup> /min	33
Piping	Length (Odu/Idu)	Min	m	-
		Max	m	15
	Elevation (Odu/Idu)	Max	m	10
Piping Connection	Liquid	OD(Outside)	mm	6.35
		OD(Outside)	inch	1/4
	Gas	OD(Outside)	mm	9.52
		OD(Outside)	inch	3/8
	Drain	OD(Outside)	mm	21.5
OD(Outside)		inch	0.85	
Refrigerant	Type			R410A
	Charge at 7.5m		g	1000
	Additional charge		g/m	20
Fan Motor Output			W	43
Compressor Type				Rotary
Net Weight			kg	34
Dimension			mm	770*545*288

\* S : Sleep / L : Low / M : Medium / H : High

\*\* Specification, design and feature are subject to change without prior notice.

\*\*\* This product contains Fluorinated greenhouse gases (R410A).